Food and Drug Administration, HHS

rating of 0.2 micron (0.45 micron if the manufacturing conditions so dictate) shall subsequently be used to reduce the content of particles in the injectable drug product. The use of an asbestos-containing filter is prohibited.

[73 FR 51932, Sept. 8, 2008]

Subpart E—Control of Components and Drug Product Containers and Closures

§211.80 General requirements.

- (a) There shall be written procedures describing in sufficient detail the receipt, identification, storage, handling, sampling, testing, and approval or rejection of components and drug product containers and closures; such written procedures shall be followed.
- (b) Components and drug product containers and closures shall at all times be handled and stored in a manner to prevent contamination.
- (c) Bagged or boxed components of drug product containers, or closures shall be stored off the floor and suitably spaced to permit cleaning and inspection.
- (d) Each container or grouping of containers for components or drug product containers, or closures shall be identified with a distinctive code for each lot in each shipment received. This code shall be used in recording the disposition of each lot. Each lot shall be appropriately identified as to its status (i.e., quarantined, approved, or rejected).

§211.82 Receipt and storage of untested components, drug product containers, and closures.

- (a) Upon receipt and before acceptance, each container or grouping of containers of components, drug product containers, and closures shall be examined visually for appropriate labeling as to contents, container damage or broken seals, and contamination.
- (b) Components, drug product containers, and closures shall be stored under quarantine until they have been tested or examined, whichever is appropriate, and released. Storage within

the area shall conform to the requirements of §211.80.

 $[43\ FR\ 45077,\ Sept.\ 29,\ 1978,\ as\ amended\ at\ 73\ FR\ 51932,\ Sept.\ 8,\ 2008]$

§211.84 Testing and approval or rejection of components, drug product containers, and closures.

- (a) Each lot of components, drug product containers, and closures shall be withheld from use until the lot has been sampled, tested, or examined, as appropriate, and released for use by the quality control unit.
- (b) Representative samples of each shipment of each lot shall be collected for testing or examination. The number of containers to be sampled, and the amount of material to be taken from each container, shall be based upon appropriate criteria such as statistical criteria for component variability, confidence levels, and degree of precision desired, the past quality history of the supplier, and the quantity needed for analysis and reserve where required by §211.170.
- (c) Samples shall be collected in accordance with the following procedures:
- (1) The containers of components selected shall be cleaned when necessary in a manner to prevent introduction of contaminants into the component.
- (2) The containers shall be opened, sampled, and resealed in a manner designed to prevent contamination of their contents and contamination of other components, drug product containers, or closures.
- (3) Sterile equipment and aseptic sampling techniques shall be used when necessary.
- (4) If it is necessary to sample a component from the top, middle, and bottom of its container, such sample subdivisions shall not be composited for testing.
- (5) Sample containers shall be identified so that the following information can be determined: name of the material sampled, the lot number, the container from which the sample was taken, the date on which the sample was taken, and the name of the person who collected the sample.
- (6) Containers from which samples have been taken shall be marked to

§211.86

show that samples have been removed from them.

- (d) Samples shall be examined and tested as follows:
- (1) At least one test shall be conducted to verify the identity of each component of a drug product. Specific identity tests, if they exist, shall be used.
- (2) Each component shall be tested for conformity with all appropriate written specifications for purity, strength, and quality. In lieu of such testing by the manufacturer, a report of analysis may be accepted from the supplier of a component, provided that at least one specific identity test is conducted on such component by the manufacturer, and provided that the manufacturer establishes the reliability of the supplier's analyses through appropriate validation of the supplier's test results at appropriate intervals.
- (3) Containers and closures shall be tested for conformity with all appropriate written specifications. In lieu of such testing by the manufacturer, a certificate of testing may be accepted from the supplier, provided that at least a visual identification is conducted on such containers/closures by the manufacturer and provided that the manufacturer establishes the reliability of the supplier's test results through appropriate validation of the supplier's test results at appropriate intervals.
- (4) When appropriate, components shall be microscopically examined.
- (5) Each lot of a component, drug product container, or closure that is liable to contamination with filth, insect infestation, or other extraneous adulterant shall be examined against established specifications for such contamination.
- (6) Each lot of a component, drug product container, or closure with potential for microbiological contamination that is objectionable in view of its intended use shall be subjected to microbiological tests before use.
- (e) Any lot of components, drug product containers, or closures that meets the appropriate written specifications of identity, strength, quality, and purity and related tests under paragraph (d) of this section may be approved and

released for use. Any lot of such material that does not meet such specifications shall be rejected.

[43 FR 45077, Sept. 29, 1978, as amended at 63 FR 14356, Mar. 25, 1998; 73 FR 51932, Sept. 8, 2008]

§ 211.86 Use of approved components, drug product containers, and closures.

Components, drug product containers, and closures approved for use shall be rotated so that the oldest approved stock is used first. Deviation from this requirement is permitted if such deviation is temporary and appropriate.

§ 211.87 Retesting of approved components, drug product containers, and closures.

Components, drug product containers, and closures shall be retested or reexamined, as appropriate, for identity, strength, quality, and purity and approved or rejected by the quality control unit in accordance with §211.84 as necessary, e.g., after storage for long periods or after exposure to air, heat or other conditions that might adversely affect the component, drug product container, or closure.

§ 211.89 Rejected components, drug product containers, and closures.

Rejected components, drug product containers, and closures shall be identified and controlled under a quarantine system designed to prevent their use in manufacturing or processing operations for which they are unsuitable.

§211.94 Drug product containers and closures.

- (a) Drug product containers and closures shall not be reactive, additive, or absorptive so as to alter the safety, identity, strength, quality, or purity of the drug beyond the official or established requirements.
- (b) Container closure systems shall provide adequate protection against foreseeable external factors in storage and use that can cause deterioration or contamination of the drug product.